



THENEW

# BYD SEAL





3.85 (0-100km/h)



Driving Range (NEDC) 650KM



DiSus-C Intelligent Damping Body Control System (Active Suspension)

### Latest Enhancement in The New BYD SEAL



19" Alloy Rim with Red Colour Brake Caliper



Electric Sunshade for Panoramic Sunroof



BYD Digital Key (NFC+Bluetooth)

Dimensions         Premium         Performance           Overall length (mm)         4,800           Overall length (mm)         1,875           Overall height (mm)         1,460           Wheel track - front / rear (mm)         1,620 / 1,625           Wheelbase (mm)         2,920           Minimum turning radius (m)         5.7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         53           Rear trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Privetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N·m)         360         360           Maximum power (kW)         230         390           Maximum power	THE NEW BYD SEAL SPECIFICATIONS	Extended Range	AWD	
Overall width (mm)         1,875           Overall height (mm)         1,460           Wheel track - front / rear (mm)         1,620/1,625           Wheelbase (mm)         2,920           Minimum turning radius (m)         5,7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (Nm)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum power (kW)         230         360           Maximum power (kW)         230         360           Maximum torque (Nm)         360         360           Maximum torque (Nm)         5.9         3.8           Electric range:         650         580	Dimensions		Performance	
Overall height (mm)         1,460           Wheel track - front / rear (mm)         1,620/1,625           Wheelbase (mm)         2,920           Minimum turning radius (m)         5.7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N·m)         360         360           Maximum power (kW)         230         390           Maximum torque (N·m)         360         670           Performance         Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km) <td>Overall length (mm)</td> <td>4,8</td> <td>300</td>	Overall length (mm)	4,8	300	
Wheel track - front / rear (mm)         1,620/1,625           Wheelbase (mm)         2,920           Minimum turning radius (m)         5,7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction saynchronous motor reasons and the company of the company o	Overall width (mm)	1,8	375	
Wheelbase (mm)         2,920           Minimum turning radius (m)         5.7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         53           Rear trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N-m)         /         310           Rear motor maximum power (kW)         230         230           Rear motor maximum power (kW)         230         390           Maximum power (kW)         230         390           Maximum torque (N-m)         360         670           Performance         Acceleration 0-100km/h (s)         5,9         3,8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5         9         3	Overall height (mm)	1,4	160	
Minimum turning radius (m)         5.7           Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         400         3           Rear trunk capacity (L)         400         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631         1           Traction Motor         Traction Motor         Traction Motor         All-Wheel Drive           Front motor type         /         Sauirrel cage induction asynchronus motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum power (kW)         230         390           Maximum power (kW)         230         390           Maximum torque (N·m)         360         670           Performance         Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity	Wheel track - front / rear (mm)	1,620	/1,625	
Ground clearance unladen (mm)         149         145           Front trunk capacity (L)         53         Rear trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185         Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum bower (kW)         230         230           Rear motor maximum torque (N·m)         360         360           Maximum power (kW)         230         390           Maximum torque (N·m)         360         670           Performance         Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5	Wheelbase (mm)	2,9	920	
Front trunk capacity (L)	Minimum turning radius (m)	5	5.7	
Rear trunk capacity (L)         400           Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (Nm)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (Nm)         360         360           Maximum power (kW)         230         390           Maximum torque (Nm)         360         670           Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5	Ground clearance unladen (mm)	149	145	
Kerb weight (kg)         2,055         2,185           Gross vehicle mass (kg)         2,501         2,631           Traction Motor           Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N·m)         360         360           Maximum power (kW)         230         390           Maximum torque (N·m)         360         670           Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5	Front trunk capacity (L)		53	
Cross vehicle mass (kg)	Rear trunk capacity (L)	4	00	
Traction Motor         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage indicates a spinth-ronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (N·m)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N·m)         360         360           Maximum power (kW)         230         390           Maximum torque (N·m)         360         670           Performance           Acceleration 0-100km/h (s)         5,9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5         5	Kerb weight (kg)	2,055	2,185	
Drivetrain         Rear Drive         All-Wheel Drive           Front motor type         /         Squirrel cage induction asynchronous motor           Front motor maximum power (kW)         /         160           Front motor maximum torque (Nm)         /         310           Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (Nm)         360         360           Maximum power (kW)         230         390           Maximum torque (Nm)         360         670           Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5         5	Gross vehicle mass (kg)	2,501	2,631	
Front motor type         /         Sauirrel cage industrial superindustrial superindu	Traction Motor		<b>'</b>	
Induction asynchronous motor	Drivetrain	Rear Drive	All-Wheel Drive	
Front motor maximum torque (N-m)	Front motor type	/	induction asynch-	
Rear motor type         Permanent magnet synchronous motor           Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N-m)         360         360           Maximum power (kW)         230         390           Maximum torque (N-m)         360         670           Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5         5	Front motor maximum power (kW)	/	160	
Rear motor maximum power (kW)         230         230           Rear motor maximum torque (N-m)         360         360           Maximum power (kW)         230         390           Maximum torque (N-m)         360         670           Performance           Acceleration 0-100km/h (s)         5,9         3.8           Electric range:         650         580           NEDC combined cycle (km)         WLTP combined cycle (km)           WLTP combined cycle (km)         570         520           Seating capacity         5	Front motor maximum torque (N·m)	/	310	
Rear motor maximum torque (N-m)         360         360           Maximum power (kW)         230         390           Maximum torque (N-m)         360         670           Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         VLTP combined cycle (km)         570         520           Seating capacity         5         5	Rear motor type	Permanent magnet	synchronous motor	
Maximum power (kW)         230         390           Maximum torque (Nrm)         360         670           Performance	Rear motor maximum power (kW)	230	230	
Maximum torque (Nm)         360         670           Performance	Rear motor maximum torque (N·m)	360	360	
Performance           Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         WLTP combined cycle (km)         570         520           Seating capacity         5         5	Maximum power (kW)	230	390	
Acceleration 0-100km/h (s)         5.9         3.8           Electric range:         650         580           NEDC combined cycle (km)         WLTP combined cycle (km)         570         520           Seating capacity         5         5	Maximum torque (N·m)	360	670	
Electric range:         650         580           NEDC combined cycle (km)         570         520           Seating capacity         5         5	Performance			
NEDC combined cycle (km)         570         520           Seating capacity         5         5	Acceleration 0-100km/h (s)	5.9	3.8	
WLTP combined cycle (km)         570         520           Seating capacity         5	Electric range:	650	580	
Seating capacity 5	NEDC combined cycle (km)			
	WLTP combined cycle (km)	570	520	
and the second s	Seating capacity		5	
Battery type BYD Blade Battery	Battery type	BYD Blad	de Battery	
Battery capacity (kWh) 82.56	Battery capacity (kWh)	82.56		
Chassis	Chassis			
Front suspension Double Wishbone	Front suspension	Double \	Wishbone	
Rear suspension Multi-Link	Rear suspension	Multi-Link		
BYD DiSus-C (NEW) —	BYD DiSus-C (NEW)	_	•	
Frequency Selective Damping (FSD)  shock absorbers  -		•	-	
Front disc brake Ventilated & Drilled Ventilated & Drilled	Front disc brake	Ventilated & Drilled	Ventilated & Drilled	
Rear disc brake Ventilated Ventilated	Rear disc brake	Ventilated	Ventilated	
Front brake caliper Fixed Fixed (Red Colour) [NEW]	Front brake caliper	Fixed	Fixed (Red Colour) [NEW]	
Wheel type Alloy Alloy	Wheel type	Alloy	Alloy	
Tyre size 235/45 R19 235/45 R19	Tyre size	235/45 R19	235/45 R19	

CONI	FIGURA	TIONS
------	--------	-------

CONFIGURATIONS		
New Energy		
AC charging port - Type 2 (7kW)	•	•
Portable charging cable (mode 2)	•	•
DC charging port - CCS 2 (150kW)	•	•
V2L function	•	•
V2L discharge adapter	•	•
Regenerative braking	•	•
Safety and Security		
Front airbags - driver & front passenger	•	•
Side airbags - driver & front passenger	•	•
Side curtain airbags - front & rear	•	•
Far-side airbags - driver	•	•
Side airbags - rear	•	•
Dual stage pretensioner	_	_
on front seat belts	•	•
Pretensioner on rear seat belts	•	•
Seat belt reminder - front & rear	•	•
360° camera	•	•
Front parking sensor (2 Zones)	•	•

Rear parking sensor (4 Zones)	•	•
ISOFIX Child restraint anchorage points	•	•
Electronic child lock		
Intelligent power brake system		
Electric Power Steering (DP-EPS)	•	•
Traction Control System (TCS)	•	•
Electronic Brake Force Distribution (EBD)	•	•
	•	•
Hill Hold Control (HHC)	•	•
Auto-hold	•	•
Adaptive Cruise Control (ACC)	•	•
Automatic Emergency Braking (AEB)	•	•
Lane Departure Warning (LDW)	•	•
Lane Departure Prevention (LDP)	•	•
Emergency Lane Keeping Assist (ELKA)	•	•
Intelligent Cruise Control (ICC)	•	•
Predictive Collision Warning (PCW)	•	•
TrafficSign Recognition (TSR)	•	•
Intelligent Speed Limit Information (ISLI)	•	•
Intelligent Speed Limit Control (ISLC)	•	•
Front Cross Traffic Alert (FCTA)	•	•
Front Cross Traffic Brake (FCTB)	•	•
Rear Cross Traffic Alert (RCTA)	•	•
Rear Cross Traffic Brake (RCTB)	•	
Blind Spot Detection (BSD)	•	
Door Open Warning (DOW)	•	
High Beam Assist (HMA)	•	
Driver Attention Warning (DAW)	•	•
Head-Up Display (W-HUD)	•	
Intelligence Torque Adaption	_	
Control (ITAC)		
Exterior		
Panoramic glass roof	•	
Electric Sunshade	•	
Electronic hidden door handles	•	•
Rear windscreen mount antenna	•	
One-touch open/close tailgate	•	•
Electrically heated and adjustable exterior mirrors		
Electrically retractable exterior mirrors	•	
Door mirror auto-tilt	•	
Door mirror position memory	•	•
Auto windows with anti-trap	•	
Soundproof double glazed glass	•	•
- windshield and front door		
Rear windscreen with electric		
heating and defrosting		
Interior		
Steering wheel mounted controls - Audio,	•	
phone, ACC and Multi-Function display		
Genuine leather-wrapped steering wheel	-	_
10.25-inch LCD instrumentation	•	•
Sunglass Holder	•	•
Centre console storage compartment	•	•
Genuine leather-wrapped seats	•	•
Driver seat 8-way power adjustable		-
Driver seat 4-way lumber power adjustment	•	•
Passenger seat 6-way power adjustable	•	•
Front seats ventilated & heated	•	•
Driver seat with position memory	•	•
Courtesy seating		
	•	•
Vice dashboard with dual cup holders	•	•
Front height-adjustable cup holder		
	•	•

Automatic anti-dazzle interior	•	
rearview mirror		
Rain-sensing frameless wipers	•	
Metal door sill protectors	•	
Front sunvisor with vanity mirror & lighting	•	
Entertainment		
FM Radio	•	
*Apple CarPlay® (wireless) and Android Auto™ (wireless)	•	
*Bluetooth® phone connectivity		
and audio streaming		
15.6-inch intelligent rotating touch		
screen display		
DYNAUDIO, 12 speakers	•	
Voice assistant - English	•	_
*Satellite navigation		
*Music streaming	-	
1 x USB-C & 1 x USB-A, Front		
1 x USB-C & 1 x USB-A, Rear	-	_
OTA updates	-	
Light		
LED headlight		
Follow me home headlight	•	
LED daytime running light	-	
LED tail light	-	_
Rear fog light		_
Sequential rear indicators	•	_
LED centre high mount stop light	•	
RGB dynamic mood lights	•	_
with rhythm function	-	
LED front reading light		
LED rear side reading light	•	
Luggage compartment light	•	_
Comfort and convenience		
Keyless entry & start	•	
NFC card key	•	
Digital Key (NFC + Bluetooth®) [NEW]	•	
Wireless phone charger × 2	•	
12V accessory socket	•	
PM2.5 high efficiency filter	•	
Negative ion air purifier	•	
Automatic dual-zone heat pump	•	
air-conditioning		
Rear central air vents	•	
Tyre repair kit	•	
Emergency kit	•	
Tool kit	•	_

- Notice

   The real range is influenced by many factors such as individual driving style, load, traffic etc. The declared range is estimated for reference only.

   Bluetooth' is a registered trademark of Bluetooth SIG, Inc. Compatibility and functionality varies depending on device.

   Apple CarPlay' is a registered trademark of Apple Inc. Requires compatible device, wrieless connection.

   Android Auto-" is a registered trademark of Google Inc. Requires compatible device, wrieless connection.

   Music streaming requires data usage or over Wi-Fi.

   Colors depicted are a guide only and may vary from actual colors due to the printing.

   Driving assist system are not a substitute for the driver's responsibility of the vehicle.

   BVD reserves the right to vary vehicle specifications and standard features from those detailed in this brochure.

#### **EXTERIOR COLOR OPTIONS**







BYD Cheras BYD Putrajaya

BYD Seremban







(with dual cup holders)

INTERIOR

COLOR




**DIMENSIONS** 















ර 🎯 f BYD - Millennium Motors



#### PRICE PACKAGE\* THE NEW BYD SEAL PREMIUM PERFORMANCE BYD SEAL (WEST MALAYSIA) Personal Company Personal Company RECOMMENDED RETAIL PRICE (RRP) RM171,800 RM191.800 Exempted (Subject to government BEV ROADTAX (1 YEAR) **REGISTRATION FEES** RM300 RM500 RM300 RM500 HP OWNERSHIP ENDORSEMENT FEES RM50 (Additional charges apply for express service from the government appointed supplier.) **EV PLATE FEES (INCLUDING BASE PLATE)** RM150 INSPECTION FEES (B2) RM200 ON-THE-ROAD PRICE RM172,500 RM172,700 RM192,500 RM192,700 (WITHOUT INSURANCE)

#### SERVICE PACKAGE\*\* 3 YEARS RM2,688,00 RM2,888.00 **STANDARD** Tyre Alignment, Balancing and Rotation Reducer Oil Service Air Conditioning Filter Service Brake Fluid Service Drive Motor Coolant Service Air Conditioning Refrigerant Service RM7,288,00 6 YEARS RM7,888,00 RVEADS RM10,488,00 RM10,888,00 **PLUS** 6 YEARS RM12.688.00 RM13.988.00 Additional: • Wiper Blades Replacement • 12V Battery Replacement • Brake Pads Replacement (Front & Rear) 8 YEARS RM20,688.00 RM22,288.00

### WARRANTY PACKAGE\*

6 YEARS or 150,000KM

**Vehicle Warranty** 

8 YEARS or 150,000KM

**Drive Unit Warranty** 

(Motor, Motor Controller, DC Assembly, High Voltage Electric Control Assembly

8 YEARS or 160,000KM

High-Voltage **Blade Battery Warranty** 

**3 YEARS** or 60,000KM

- Dust Cover

- · AC/DC Charging Port Assembly

4 YEARS or 100,000KM

- Whole Vehicle Lights
- Suspension

\*Terms & Conditions Apply: 1) Sime Darby Beyond Auto reserves all rights to change the Recommended Retail Price

- and specifications of the car.

  2) Registration fees above is for Malaysian. Non-Malaysian fees are varied from above.
- 3) Prices are valid in Peninsular Malaysia, except Langkawi.
  4) Prices are effective from 22nd September 2025, based on the Recommended Retail Price,
- 5) The offer above is not applicable with other promotions, unless stated otherwise.

- Prices will remain valid until a written notice or new price list is issued by Sime Darby Beyond Auto. Sime Darby Beyond Auto reserves the right to change prices without prior notice.
- The services included in each package may vary based on maintenance requirements as specified in the warranty booklet.

♠ BYD KL North BYD Bandar Utama **BYD Cheras** BYD Putrajaya

**BYD Seremban** 

© 012-8228645

in BYD-Millennium Autobeyond Sdn Bhd

ਰੇ 🎯 🗲 BYD - Millennium Motors BYD Millennium千禧









**AURORA WHITE** 

**SHARK GREY** 







**COSMOS BLACK** 

### BYD SEAL

## **5 YEAR** MONTHLY

PREMIUM from RM2,885
PERFORMANCE from RM3,220

## **7 YEAR** MONTHLY

PREMIUM from RM2,146
PERFORMANCE from RM2,395

## **9 YEAR** MONTHLY

PREMIUM from RM1,735
PERFORMANCE from RM1,936

### **10% DOWN PAYMENT**